45 Series 4590

Acqua calda
Hot Water

Per uso frequente
For frequent usage

Accessori professionali
Professional accessories

TSS® Total Stop SYSTEM



Caratteristiche Generali - *General Features:*

- Pompa a 3 pistoni in ceramica con sistema biella-manovella
- Testa pompa in ottone
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico a induzione con protezione termica
- Sistema di arresto totale dell' idropulitrice a distanza
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale, doppia serpentina e fondo in materiale refrattario
- Serbatoio gasolio 4 l
- Filtro acqua e filtro aspirazione gasolio
- Lunghezza cavo elettrico 5 m

- *3 Axial stainless steel pistons wobble-plate pump with aluminium head*
- *Brass pump head*
- *Automatic by-pass valve with pump head pressure discharge*
- *Single-phase induction electric motor with thermal protector*
- *Remote Total Stop System of the cleaner*
- *With safety pressure switch to shut down the boiler in case of lack of water*
- *Vertical boiler with double heating coil and refractory compound base*
- *Fuel tank capacity 4 l*
- *Water filter and fuel inlet filter*
- *Electric cable length 5 m*

Fornito con - *Equipped with:*

AL 15
Pistola 3/8"(M) M22x1,5 (100° C)
Trigger gun
(41047)



(0,5 l)
Kit schiumogeno con serbatoio
Foam lance bottle
(40320)





Lancia
Lance
(50690)




Ugello 1/4 MEG
Wash nozzle
(3104) - (1503)

Tubo AP 8 m armato
8 m reinforced HP hose
max 155°C - 250 bar
(50689)











(HPV)

Dati Tecnici / *Technical Data*													
MOD	COD	MAX		lt/h									kg
		bar	psi	l/h	gph	kW	rpm	Hz	V	°C	°C Max	Δ°t	kg
4590	**24426**	150	2200	500	132	2,5	2800	1~50	230	30	90	45	52,8

Temperatura massima acqua / *Max inlet water temperature* 50°C 122°F - IPX5-S1